AD-A253 810

PAGE

Form Approved OMB No 0704-0188



comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED			
	07/92	POP Test (06/92)			
4. TITLE AND SUBTITLE Performance Oriented Packaging Shipping and Storage, Mk 211 if for Packing Group II Solid Hazard 6. AUTHOR(8) J. Mike Dwyer	SELECTE AUG 3 1992				
7. PERFORMING ORGANIZATION NAME Naval Weapons Station Earle Test and Evaluation Branch (Coc Colts Neck, NJ 07722-5000		8. PERFORMING ORGANIZATION REPORT NUMBER DODPOPHM/USA/DOD/NADTR92014			
9. SPONSORING/MONITORING AGENCY Commander, Naval Sea Systems Department of the Navy Washington, DC 20362-5101		10. SPONSORING/MONITORING AGENCY REPORT NUMBER Same as above			
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AMAILABILITYPSTA	rent has been approved release and sale; its is unlimited.	12b. DISTRIBUTION CODE			

13. ABSTRACT (Maximum 200 words)

This Performance Oriented Packaging (POP) test was conducted to ascertain whether the Mk 211 Mod 3 Shipping and Storage Container meets the Packing Group II requirements specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 1 October 1991. The packaged commodity used for the test was a simulated inert warhead section weighing 65 kg (143 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in product and/or packaging, 13 kg (28 pounds) were added. Gross weight of the loaded container was 118 kg (260 pounds). The test results indicate that the container has conformed to the POP requirements.

In addition, due to their similarities in design, size, and weight, this test is considered representative of qualification testing for the Mk 567 Mod 0 Shipping and Storage Containers as per the variation in Title 49 CFR 107, Sec. 178.601h.

14. SUBJECT TERMS		16. NUMBER OF PAGES 7 16. PRICE CODE					
POP Test of Mk 211 Mod 3 and and Storage Container	Mk 567 Mod 0 Shipping						
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICA- TION OF THIS PAGE	19. SECURITY CLASSIFICA- TION OF ABSTRACT	20. LIMITATION OF ABSTRACT				
UNCLASSIFIED	UL	UL	UL				

DODPOPHM/USA/DOD/NADTR92014


PERFORMANCE ORIENTED PACKAGING TESTING OF CONTAINER, SHIPPING AND STORAGE, MK 211 MOD 0 AND MK 567 MOD 0 FOR PACKING GROUP II SOLID HAZARDOUS MATERIALS

DTIC QUALITY INSPECTED 8

Author:
J. Mike Dwyer
Mechanical Engineering Technician

Performing Activity:
Naval Weapons Station Earle
Colts Neck, New Jersey 07722-5000

July 1992



FINAL

DISTRIBUTION UNLIMITED



Sponsoring Organization:
Naval Sea Systems Command (PMS-422)
Department of the Navy
Washington, DC 20362-5101

92 8 3

INTRODUCTION

This Performance Oriented Packaging (POP) test was performed to ascertain whether the Mk 211 Mod 3 Shipping and Storage Container (Packing Group II) meets the requirements specified by the United Nations Recommendation on the Transportation of Dangerous Goods Document, ST/SG/AC.10/1, Revision 6, Chapters 4 and 9 and the Code of Federal Regulations, Title 49 CFR, Parts 107 through 178, dated 1 October 1991. The packaged commodity used for the test was a simulated inert warhead section weighing 65 kg (143 pounds). This represents the current maximum commodity weight. To compensate for future growth variations in product and/or packaging, 13 kg (28 pounds) were added. Gross weight of the loaded container was 118 kg (260 pounds).

Due to unavailability only one container was used for testing. This is less than the number required by the regulations. Approval for this deviation has been granted by the Under Secretary of Defense, Memorandum for the Joint Logistics Commanders dated 22 February 1990.

In addition, due to their similarities in design, size, and weight, this test is considered representative of qualification testing for the Mk 567 Mod 0 Shipping and Storage Containers as per the variation in Title 49 CFR 107, Sec. 178.601h.

TESTS PERFORMED

1. Base Level Vibration Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.608. The container was placed on a repetitive shock platform which has a vertical linear motion of 1-inch double amplitude. Movement of the container was restricted during vibration in all but the vertical direction. The frequency of the platform was increased until the container left the platform 1/16 of an inch at some instant during each cycle. Test time was 1 hour.

2. Stacking Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.606. The container was subjected to a force applied to its top surface equivalent to the total weight of identical packages stacked to a minimum height of 3 meters (including the test container). A weight of 354 kg (780 pounds) was stacked on the test container. The test was performed for 24 hours. The weight was then removed and the container examined.

3. Drop Test

This test was performed in accordance with Title 49 CFR, Part 178, Subpart M, Sec. 178.603. Six drops were performed from a height of 1.2 meters (4 feet) in the following orientations (three drops for each orientation):

DODPOPHM/USA/DOD/NADTR92014

- a. Horizontally.
- b. Diagonally on the edge between the cover assembly and the top ring of the container.

PASS/FAIL

1. Base Level Vibration Test

The criteria for passing the base level vibration test is outlined in Title 49 CFR, Sec. 178.608(c): No test sample should show any deterioration which could adversely affect transportation safety or any distortion liable to reduce packaging strength.

2. Stacking Test

The criteria for passing the stacking test is outlined in Title 49 CFR, Sec. 178.606(d): No test sample may show any deterioration which could adversely affect transportation safety or any distortion likely to reduce its strength, cause instability in stacks of packages, or cause damage to inner packagings likely to reduce safety in transportation.

3. Drop Test

The criteria for passing the drop test is outlined in Title 49 CFR, Sec. 178.603(f): A package is considered to successfully pass the drop tests if for each sample tested, no rupture occurs which would permit spillage of loose explosive substances or articles from the outer packaging.

TEST RESULTS

1. Base Level Vibration Test

Satisfactory.

2. Stacking Test

Satisfactory.

3. Drop Test

Satisfactory.

DISCUSSION

1. Base Level Vibration Test

The input vibration frequency was 3.5 Hz. Immediately after the vibration test was completed, the container was removed from the platform, turned on its side and inspected. No unfavorable distortion or deterioration was observed.

2. Stacking Test

The container was inspected after the 24-hour period was over. No unfavorable distortion or deterioration was observed.

3. Drop Test

After each drop, the container was inspected. The warhead was completely retained by the container.

REFERENCE MATERIAL

- A. United Nation's "Recommendation on the Transportation of Dangerous Goods," ST/SG/AC.10/1, Revision 6.
 - B. Code of Federal Regulations, Title 49 CFR, Parts 107-178.
- C. Bureau of Explosives Tariff No. BOE 6000K Hazardous Materials Regulations of the Department of Transportation by Air, Rail, Highway, Water including Specifications for Shipping Containers.

DISTRIBUTION LIST

Defense Technical Information Center (2 copies) ATIN: DTIC/FDA

Bldg. 5, Cameron Station

Alexandria, VA 22304-6145

Defense General Supply Center ATTN: DDRV-TMPA, D. Gay Richmond, VA 23219

Commander

ATTN: Crane Division (Code 4053)

Naval Surface Warfare Center

Crane, IN 47522-5000

TEST DATA SHEET

POP MARKING:

UN 1A2/Y118/S/**/USA/DOD/NAD

**YEAR LAST PACKED OR MANUFACTURED

DATA SHEET:

Container: Mk 211 Mod 3 and Mk 567 Mod 0 Shipping and Storage Container

Type: 1A2 Container P/N or NSN: N00197-88-C-0035

Specification Number: DL 5166851 Material: Steel

Gross Weight: 118 kg (260 pounds) | Dimensions: 20.25" W x 33.13" H

Closure (Method/Type): Tare Weight:
Cover and Locking Ring 40 kg (89 pounds)

Additional Description:

PRODUCT:

Nama: See table 1 NSN(s): See table 1

United Nations Number: See table 1

United Nations Packing Group: II

Physical State (Solid, Liquid, or Gas): Solid

Vapor Pressure (Liquids Only): N/A At 50 °C: N/A At 55 °C: N/A

Consistency/Viscosity: N/A Density/Specific Gravity: N/A

Amount Per Container: See table 1 Flash Point: N/A

Net Weight: See table 1

TEST PRODUCT:

Name: Warhead (Inert) Physical State: Solid

Consistency: N/A Density/Specific Gravity: N/A

Test Pressure (Liquids Only): N/A

Amount Per Container: N/A | Net Weight: 77 kg (171 pounds)

Additional Description:

The net weight includes the current maximum product weight plus an additional

13 kg (28 pounds).

TABLE 1
Products Approved for Shipping in the
Mk 211 Mod 3 Shipping and Storage Container

NALC/ DODIC	NSN	Product Nomenclature	Packing Drawing Number	Haz Class/Div	UN Number	Units/ Cntr	Totel Net Weight (lb)	Total Gross Weight (lb)
V453	1336-00-398-9993	Warhead, Mk 90/0	5166865	1.10	0286	1	143.0	232.0
V356	1336-00-060-8797	Warhead, Mk 51/1	5166865	1.1D	0286	1	142.0	231.0
YW87	1336-01-136-7603	Warhead, Mk 115/0	5166865	1.1D	0286	1	91.0	180.0
V991	1336-01-297-7318	Warhead, Mk 115/1	5166865	1.1D	0286	1	138.0	227.0

Mk 567 Mod 0 Shipping and Storage Container

NALC/ DODIC	NSN	Product Nomenclature	Packing Drawing Number	Haz Class/Div	UN Number	Units/ Cntr	Total Net Weight (lb)	Total Gross Weight (lb)
ZW48	1336-00-193-5247	ANDKT 27	2644737	N/A	N/A	1	138.0	184.0
ZW33	1336-00-465-9239	ANDKT 26	2644736	N/A	N/A	1	139.0	185.0
JW58	1336-01-088-8022	ANDKT 42	2844737	N/A	N/A	1	139.0	185.0

N/A = Not Assigned